



TMT-9000S





Soldering & Rework Station



TMT-9000S COMPONENTS

TMT-9000PS	Power Supply
SHH-1	Soldering Handpiece Holder
SHP-1	Soldering Handpiece
RMP-1	Tip Removal Pad
SG-1-GR	Handpiece Grip Green
SG-1-GY	Handpiece Grip Gray
BC-1	Brass Curls
SPG-1	Sulphide Free Sponge
M7CH176	Soldering tip cartridge


TMT-9000S SPECIFICATIONS

Input Line Voltage: TMT-9000PS-1	100-110 VAC
TMT-9000PS-2	220-240 VAC
Tip to Ground Potential:	<2mV, true RMS 50-500Hz
Tip to Ground Resistance:	<2 Ohms DC
Idle temperature Stability:	+/- 1.1°C (2 °F)
Ambient Operating Temperature:	10-40 °C (50 °F -104 °F)
Maximum Enclosure Temperature:	50 °C (122 °F)
Fuse: TMT-9000PS-1	125V 1A "Slo-Blo"
TMT-9000PS-2	250V 0.5A "Slo-Blo"
Output Power (Maximum):	40 Watts
Output Frequency:	13.56 MHz
Size (W x H x D):	212.4mm x 118mm x 132mm
Weight:	3.47 KG
LCD display:	60mm x 16mm
Input Line Frequency:	50/60 Hz
Certification marks:	   

ACCESSORY - DESOLDER GUN



DSKIT-1



Part Number	A		B	
	MM	IN.	MM	IN.
M75DT003	0.8	0.03"	1.3	0.05"
M75DT004	1.0	0.04"	1.6	0.06"
M75DT005	1.3	0.05"	2	0.08"