


K80CS005



K80CS005

ESD LEAD

Conical Sharp 0.5mm (0.02")

▶ Tip Style: Conical Sharp▶ Tip Width: 0.50mm (0.02")▶ Tip Length: 11.80mm (0.46")

DESCRIPTION


Based on Curie Heat Technology, K Series Tips respond to the thermal demands of each solder joint instantaneously, provide excellent heat transfer and excellent durability. 80 Series tips are designed for high thermal demand soldering applications.

SPECIFICATIONS

80 Type Cartridge ¹ :	420°C - 475°C				
RoHS Compliant ² / Lead Free:	YES				
For Use With:	TMT-1000S-K, w/SHP-KM, PS9		TMT-2200S-2KM,	MFR	Systems

MATERIAL COMPOSITION







All components are RoHS compliant and Lead-Free.

- 1 Thermaltronics tip cartridges will typically idle within a temperature range of +/-1.1°C. However, there is variation in idle temperature across tip geometries within an individual temperature series. Thermaltronics offers a wide variety of tip geometries from 0.10mm fine point tip to 30mm blade tips. The length and geometry of a tip will have an influence on the tip idle temperature. To accurately measure idle temperature it will depend greatly on the measurement method, technique and equipment used. Two different methods or the use of alternative equipment will produce different test results.
- 2 Please refer to European Commission for details on RoHS Compliance.